




NUMINOS® DL S

Indoor LED recessed ceiling light white/white 2700K
20°, including leaf springs

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. This also includes NUMINOS® DL S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 8.6 watts, luminous flux of 720 lumens, colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



Tekniske data

Item no.	1003782
Antal lysåbninger	1
IP klasse	IP20/IP44
IK Vandalklasse	IK02
Slagfæsthed	0.2 Joule
Montering	Recessed
Monterings detaljer	Ceiling
Sekundær strøm / spænding	250mA
IP Tæthedsgrad	III
Watt	8.6 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	720 lm
Farvetemperatur	2700 Kelvin
Spredningsvinkel	20 °
Farve	white
CRI	90
UGR ≤	18.5
LXXBXX-data	L80B50
Højde	5.2 cm
Diameter	8 cm
Nettovægt	0.165 kg

Lyskilde

791819	
Tilbehør	
1006136	Numinos® XS Reducing ring , round 160/70mm white
1006458	LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI
1006135	Numinos® XS Reducing ring , round 160/70mm black
1004789	NUMINOS® S , diffuser Wabe
1004067	LED driver , 15W 250mA DALI
1004788	NUMINOS® S , diffuser Frosted
1004787	NUMINOS® S , diffuser Prisma
1004786	NUMINOS® S , diffuser Ellipse
1006454	RF module Casambi for LED bridge driver , single colour
1004058	LED driver , 6.5-10W 250mA
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006137	Numinos® XS Reducing ring , square 160/70mm black
1006138	Numinos® XS Reducing ring , square 160/70mm white
1004055	LED driver , 6.5-10W 250mA PHASE

Bruttovægt	0.194 kg
Indbygningsdybde	5.5 cm
Installations diameter	6.8 cm
BIG WHITE side	87