




## NUMINOS® DL S

Indoor LED recessed ceiling light black/black 3000K  
55° gimballed, rotating and pivoting, including leaf  
springs

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® DL S recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 8.6 watts, luminous flux of 690 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?



### Tekniske data

|                           |             |
|---------------------------|-------------|
| Item no.                  | 1003799     |
| Antal lysåbninger         | 1           |
| IP klasse                 | IP20/IP44   |
| IK Vandalklasse           | IK02        |
| Slagfaste                 | 0.2 Joule   |
| Montering                 | Recessed    |
| Monterings detaljer       | Ceiling     |
| Sekundær strøm / spænding | 250mA       |
| IP Tæthedegrad            | III         |
| Watt                      | 8.6 W       |
| Min omgivelsestemperatur  | -20 °C      |
| Max omgivelsestemperatur  | 40 °C       |
| Lumen                     | 690 lm      |
| Farvetemperatur           | 3000 Kelvin |
| Spredningsvinkel          | 55 °        |
| Farve                     | black       |
| CRI                       | 90          |
| UGR ≤                     | 22          |
| LXXBXX-data               | L80B50      |
| Højde                     | 5.2 cm      |
| Diameter                  | 8 cm        |
| Nettovægt                 | 0.163 kg    |

Lyskilde

|          |                                                                                            |
|----------|--------------------------------------------------------------------------------------------|
| 791815   |           |
| Tilbehør |                                                                                            |
| 1006136  | Numinos® XS Reducing ring , round 160/70mm white                                           |
| 1006458  | LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI |
| 1006135  | Numinos® XS Reducing ring , round 160/70mm black                                           |
| 1004789  | NUMINOS® S , diffuser Wabe                                                                 |
| 1004067  | LED driver , 15W 250mA DALI                                                                |
| 1004788  | NUMINOS® S , diffuser Frosted                                                              |
| 1004787  | NUMINOS® S , diffuser Prisma                                                               |
| 1004786  | NUMINOS® S , diffuser Ellipse                                                              |
| 1006454  | RF module Casambi for LED bridge driver , single colour                                    |
| 1004058  | LED driver , 6.5-10W 250mA                                                                 |
| 1006199  | RF module Zigbee for DALI LED bridge driver , single colour                                |
| 1006137  | Numinos® XS Reducing ring , square 160/70mm black                                          |
| 1006138  | Numinos® XS Reducing ring , square 160/70mm white                                          |
| 1004055  | LED driver , 6.5-10W 250mA PHASE                                                           |

|                        |          |
|------------------------|----------|
| Bruttovægt             | 0.195 kg |
| Indbygningsdybde       | 5.5 cm   |
| Installations diameter | 6.8 cm   |
| BIG WHITE side         | 87       |