



## NUMINOS® DL S

**Indoor LED recessed ceiling light black/white 3000K  
55° gimballed, rotating and pivoting, including leaf  
springs**

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. The diverse downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® DL S recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 8.6 watts, luminous flux of 730 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.

## TECHNICAL DATA

Item no.	1003800
Number of different light outlets	1
IP Code	IP 20 / IP 44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	250 mA
Safety class	III
Wattage	8.6 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	730 lm
Colour temperature	3000 Kelvin
Beam angle	55 °
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct

## Light Source

791815	
--------	---

### Accessories

1006136	Numinos® XS Reducing ring , round 160/70mm white
1006458	LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI
1006135	Numinos® XS Reducing ring , round 160/70mm black
1004789	NUMINOS® S , diffuser Wabe
1004067	LED driver , 15W 250mA DALI
1004788	NUMINOS® S , diffuser Frosted
1004787	NUMINOS® S , diffuser Prisma
1004786	NUMINOS® S , diffuser Ellipse
1006454	RF module Casambi for LED bridge driver , single colour
1004058	LED driver , 6.5-10W 250mA
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006137	Numinos® XS Reducing ring , square 160/70mm black
1006138	Numinos® XS Reducing ring , square 160/70mm white
1004055	LED driver , 6.5-10W 250mA PHASE

Risk Group	1
Height	5.2 cm
Diameter	8 cm
Net weight	0.16 kg
Gross weight	0.2 kg
Shape of cut-out	round
Installation depth	5.5 cm
Installation diameter	6.8 cm
BIG WHITE Page	87