




NUMINOS® DL L

Indoor LED recessed ceiling light white/chrome 2700K 20°

The NUMINOS light system from SLV perfectly combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® DL L recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 25.41 watts, luminous flux of 2150 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



Tekniske data

Item no.	1003927
Antal lysåbninger	1
IP klasse	IP20/IP44
IK Vandalklasse	IK02
Slagfæsthed	0.2 Joule
Montering	Recessed
Monterings detaljer	Ceiling
Sekundær strøm / spænding	700mA
IP Tæthedsgard	III
Watt	25.41 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	2150 lm
Farvetemperatur	2700 Kelvin
Spredningsvinkel	20 °
Farve	white/chrome
CRI	90
UGR ≤	19
LXXBXX-data	L80B50
Højde	8.5 cm
Diameter	13 cm
Nettovægt	0.473 kg

Lyskilde

791800	
Tilbehør	
1004062	LED driver , 21-29.5W 500/600/700mA for Numi- nos Downlight Serie
1004795	NUMINOS® L , diffuser Prisma
1004796	NUMINOS® L , diffuser Frosted
1006143	Numinos® M Reducing ring , round 240/120mm black
1006460	LED bridge driver , 42W, 700mA for NUMINOS®, including radio interface for RF module, DALI
1004794	NUMINOS® L , diffuser Ellipse
1006146	Numinos® M Reducing ring , square 240/120mm white
1006454	RF module Casambi for LED bridge driver , single colour
1006144	Numinos® M Reducing ring , round 240/120mm white
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1004070	LED driver , 40W 700mA DALI
1006145	Numinos® M Reducing ring , square 240/120mm black
1004797	NUMINOS® L , diffuser Wabe
1004065	LED driver , 30W 700mA

Bruttovægt	0.542 kg
Indbygningsdybde	9 cm
Installations diameter	11.7 cm
BIG WHITE side	87