



NUMINOS® DL L

Indoor LED recessed ceiling light black/chrome 3000K 40°

The NUMINOS light system from SLV perfectly combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® DL L recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light convinces with a power consumption of 25.41 watts, luminous flux of 2200 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

Item no.	1003942
Number of different light outlets	1
IP Code	IP 20 / IP 44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Wattage	25.41 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	2200 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct

Light Source

791822	
--------	---

Accessories

1004062	LED driver , 21-29.5W 500/600/700mA for Numinos Downlight Serie
1004795	NUMINOS® L , diffuser Prisma
1004796	NUMINOS® L , diffuser Frosted
1006143	Numinos® M Reducing ring , round 240/120mm black
1006460	LED bridge driver , 42W, 700mA for NUMINOS®, including radio interface for RF module, DALI
1004794	NUMINOS® L , diffuser Ellipse
1006146	Numinos® M Reducing ring , square 240/120mm white
1006454	RF module Casambi for LED bridge driver , single colour
1006144	Numinos® M Reducing ring , round 240/120mm white
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1004070	LED driver , 40W 700mA DALI
1006145	Numinos® M Reducing ring , square 240/120mm black
1004797	NUMINOS® L , diffuser Wabe
1004065	LED driver , 30W 700mA

Risk Group	1
Height	8.5 cm
Diameter	13 cm
Net weight	0.465 kg
Gross weight	0.525 kg
Shape of cut-out	round
Installation depth	9 cm
Installation diameter	11.7 cm
BIG WHITE Page	87