



## NUMINOS® DL XL

Indoor LED recessed ceiling light black/black 2700K 20°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® DL XL recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 37.4 watts, luminous flux of 3300 lumens, colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. This means that simple installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.

## TECHNICAL DATA

|                                   |                      |
|-----------------------------------|----------------------|
| Item no.                          | 1003985              |
| Number of different light outlets | 1                    |
| IP Code                           | IP 20 / IP 44        |
| Impact resistance class           | IK 02                |
| Impact resistance                 | 0.2 Joule            |
| Assembly                          | Recessed             |
| Assembly details                  | Ceiling              |
| Secondary power / voltage         | 1050 mA              |
| Safety class                      | III                  |
| Wattage                           | 37.4 W               |
| Minimum ambient temperature       | -20 °C               |
| Maximum ambient temperature       | 40 °C                |
| Lumen                             | 3300 lm              |
| Colour temperature                | 2700 Kelvin          |
| Beam angle                        | 20 °                 |
| Color                             | black                |
| CRI                               | 90                   |
| UGR ≤                             | 22                   |
| LXXBXX data                       | L80B50               |
| Service life                      | 50000 h              |
| Light distribution                | rotational symmetric |
| Light outlet                      | direct               |

## Light Source

|        |   |
|--------|---|
| 791857 |  |
|--------|---|

### Accessories

|         |   |
|---------|---|
| 1006148 | Numinos® L Reducing ring , round 240/150mm white  |
| 1006149 | Numinos® L Reducing ring , square 240/150mm black   |
| 1004800 | NUMINOS® XL , diffuser Frosted  |
| 1004071 | LED driver 4.2-50W 1050mA DALI  |
| 1006150 | Numinos® L Reducing ring , square 240/150mm white   |
| 1006454 | RF module Casambi for LED bridge driver , single colour                                     |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour                                 |
| 1006147 | Numinos® L Reducing ring , round 240/150mm black  |
| 1004798 | NUMINOS® XL , diffuser Ellipse  |
| 1004059 | LED driverm 40W multi mA  |
| 1006461 | LED bridge driver , 42W, 1050mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004066 | LED driver , 28-40W 1000mA PHASE  |
| 1004801 | NUMINOS® XL , diffuser Wabe   |
| 1004799 | NUMINOS® XL , diffuser Prisma   |

|                       |          |
|-----------------------|----------|
| Risk Group            | 1        |
| Height                | 10.8 cm  |
| Diameter              | 16 cm    |
| Net weight            | 0.715 kg |
| Gross weight          | 0.87 kg  |
| Shape of cut-out      | round    |
| Installation depth    | 11.5 cm  |
| Installation diameter | 14.5 cm  |
| BIG WHITE Page        | 87       |