



NUMINOS® DL XL

Indoor LED recessed ceiling light weiß/chrome 2700K 20°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With different downlights and spotlights, you provide a thousand lighting design possibilities. This also includes NUMINOS® DL XL, which impresses as a recessed ceiling light with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 37.4 watts, luminous flux of 3400 lumens, colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

Item no.	1003999
Number of different light outlets	1
IP Code	IP 20 / IP 44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	1050 mA
Safety class	Ш
Wattage	37.4 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	3400 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR≤	19
LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct



Light Source

791857	A E	
Accessories		
1006148	Numinos® L Reducing ring , round 240/150mm white	
1006149	Numinos® L Reducing ring , square 240/150mm black	
1004800	NUMINOS® XL , diffuser Frosted	
1004071	LED driver 4.2-50W 1050mA DALI	
1006150	Numinos® L Reducing ring , square 240/150mm white	
1006454	RF module Casambi for LED bridge driver , single colour	
1006199	RF module Zigbee for DALI LED bridge driver , single colour	
1006147	Numinos® L Reducing ring , round 240/150mm black	
1004798	NUMINOS® XL , diffuser Ellipse	
1004059	LED driverm 40W multi mA	
1006461	LED bridge driver , 42W, 1050mA for NUMINOS®, including radio interface for RF module, DALI	
1004066	LED driver , 28-40W 1000mA PHASE	
1004801	NUMINOS® XL , diffuser Wabe	
1004799	NUMINOS® XL , diffuser Prisma	

Risk Group	1
Height	10.8 cm
Diameter	16 cm
Net weight	0.709 kg
Gross weight	0.88 kg
Shape of cut-out	round
Installation depth	11.5 cm
Installation diameter	14.5 cm
BIG WHITE Page	87