



3~ NUMINOS® PHASE S

3 phase system light whitek/black 2700K 24°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the 3~ NUMINOS® PHASE S 3-phase system light LED, which convinces with best workmanship and light quality. The spotlight is perfect for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 985 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

Item no.	1004078
Rotating or tilting	rotary Bar and tiltable
Assembly details	Track Ceiling,Track Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10.42 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	88
Number of luminaires at LS C16A	88
Level of inrush current	8.5 A
Duration of inrush current	60 µs
Lumen	985 lm
Colour temperature	2700 Kelvin
Beam angle	24 °
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L80B50

Light Source

791819	
--------	---

Accessories

1006167	NUMINOS® S , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	16.2 cm
Height	14.5 cm
Diameter	6.5 cm
Net weight	0.5 kg
Gross weight	0.8 kg
BIG WHITE Page	112