




## NUMINOS® S | 3Ph., PHASE

**NUMINOS® S 3Ph., PHASE, 3~ Spotlight, cylindrical, 2700 K, 8 Watt, trailing edge, 60°, matt white / matt black**

The NUMINOS® S 3-Phasen Spot is a cylindrical luminaire designed for mounting on ceiling or wall track systems. With a colour temperature of 2700 K and a beam angle of 60°, the spot is particularly suitable for targeted lighting applications indoors. The luminaire has a power consumption of 8 watts and produces a luminous flux of 950 lumens. The housing is made of aluminium and is available in matt white or matt black. Control is via phase-cut dimming. The IP20 protection rating allows use in protected indoor areas. With a product length of 16.2 cm, a diameter of 6.5 cm, and a height of 14 cm, the spot offers a compact design for flexible installations.



### Light source

2093870



|                                   |                    |
|-----------------------------------|--------------------|
| Item no.                          | 1004080            |
| Lamps included                    | No                 |
| Number of different light outlets | 1                  |
| IP Code                           | IP20               |
| Assembly                          | Track              |
| Assembly details                  | Ceiling, Wall,     |
| Dimmable                          | true               |
| Dimming technology                | trailing edge      |
| Primary nominal voltage           | 220-240V ~ 50/60Hz |
| Secondary power / voltage         | 200 mA             |
| Safety class                      | I                  |
| Wattage                           | 8 W                |
| Minimum ambient temperature       | -20°C              |
| Maximum ambient temperature       | 45°C               |
| Number of luminaires at LS B16A   | 128.0              |
| Number of luminaires at LS C16A   | 128.0              |
| Level of inrush current           | 10 A               |
| Duration of inrush current        | 50 µs              |
| Beam angle                        | 60°                |
| Color                             | white              |
| CRI                               | 90                 |
| UGR ≤                             | 19                 |
| LXXBXX data                       | L90B10             |
| Service life                      | 50 000 h           |
| Risk Group                        | 1                  |
| Length                            | 16.2 cm            |
| Height                            | 14 cm              |
| Diameter                          | 6.5 cm             |
| Net weight                        | 0.52 kg            |

## Accessories

|         |                                     |
|---------|-------------------------------------|
| 1006167 | NUMINOS® S, white front ring        |
| 1008144 | NUMINOS® S, front ring, matt gold   |
| 1008140 | NUMINOS® S, front ring, matt copper |