NUMINOS® S | CL, PHASE

NUMINOS® S CL, PHASE, Surface-mounted ceiling light, 2700 K, 8 Watt, trailing edge, 60°, matt white / matt black

The NUMINOS® S CL, PHASE is a cylindrical surface-mounted ceiling luminaire suitable for indoor use. It delivers a luminous flux of 950 lumens at a colour temperature of 2700 K and a beam angle of 60°. The luminaire features phase-cut dimming, allowing seamless adjustment of light intensity. The housing is made of aluminium and is available in matt white or matt black. With a height of 16.2 cm and a diameter of 6.5 cm, the luminaire is compactly designed. The IP20 protection rating makes it suitable for protected indoor areas. The declared service life is 50,000 hours.



Light source

2093870	A to G: D

Item no.	1004128
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	128
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	200 mA
Safety class	I
Wattage	8 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	128.0
Number of luminaires at LS C16A	128.0
Level of inrush current	10 A
Duration of inrush current	50 µs
Beam angle	60°
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Height	16.2 cm
Diameter	6.5 cm
Net weight	0.43 kg

Accessories

1006167	NUMINOS® S, white front ring
1008144	NUMINOS® S, front ring, matt gold
1008140	NUMINOS® S, front ring, matt copper