NUMINOS® M | CL, PHASE

NUMINOS® M CL, PHASE, Surface-mounted ceiling light, 2700 K, 14 Watt, trailing edge, 24°, matt white / matt black

The NUMINOS® M SPOT is a surface-mounted ceiling luminaire designed for indoor use. It features a cylindrical design and is available in matte white or matte black. The luminaire is equipped with a 14-watt LED that provides a luminous flux of 1750 lumens at a warm white colour temperature of 2700 K and a beam angle of 24°. Control is via trailing edge phase dimming. The housing is made of aluminium and polycarbonate. With a diameter of 8.5 cm, a length of 18.5 cm, and a height of 16.5 cm, the luminaire is compactly sized. The protection rating is IP20, making it suitable for dry indoor areas. The round canopy shape allows for easy ceiling installation.



Light source

2093865	A G D

Item no.	1004198
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	78
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	78.0
Number of luminaires at LS C16A	78.0
Level of inrush current	10 A
Duration of inrush current	50 µs
Beam angle	24°
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	18.5 cm
Height	16.5 cm
Diameter	8.5 cm

Accessories

1006168	NUMINOS® M, white front ring
1008145	NUMINOS® M, front ring, matt gold
1008141	NUMINOS® M, front ring, matt copper