NUMINOS® M | CL, PHASE

NUMINOS® M CL, PHASE, Surface-mounted ceiling light, 2700 K, 14 Watt, trailing edge, 60°, matt white / matt black

The NUMINOS® M SPOT is a surface-mounted ceiling luminaire characterised by its cylindrical shape and a matte finish available in white or black. It is designed for indoor use where directional lighting with a beam angle of 60° is required. The luminaire provides a luminous flux of 1750 lumens at a colour temperature of 2700 K and operates at a power of 14 watts. Dimming is achieved via phase-cut (trailing edge). The housing is made of aluminium and polycarbonate, and the luminaire is equipped with a round canopy. The protection rating is IP20, making it suitable for dry indoor areas. With a lifespan of 50,000 hours, it is designed for long-lasting use. Its compact dimensions of 18.5 cm length, 8.5 cm diameter, and 16.5 cm height allow for flexible ceiling installation.



Light source

2093865	A D

Item no.	1004200
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	78
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	78.0
Number of luminaires at LS C16A	78.0
Level of inrush current	10 A
Duration of inrush current	50 µs
Beam angle	60°
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	18.5 cm
Height	16.5 cm
Diameter	8.5 cm

Accessories

1006168	NUMINOS® M, white front ring
1008145	NUMINOS® M, front ring, matt gold
1008141	NUMINOS® M, front ring, matt copper