NUMINOS® M | CL, PHASE

NUMINOS® M CL, PHASE, Surface-mounted ceiling light, 3000 K, 14 Watt, trailing edge, 24°, matt black

The NUMINOS® M SPOT surface-mounted ceiling luminaire is designed for indoor use and is particularly suitable for targeted accent lighting. It features a cylindrical shape with a matte black aluminium housing and a polycarbonate diffuser. The luminaire operates with a luminous flux of 1800 lumens at 14 watts and a colour temperature of 3000 K, producing warm white light. The beam angle is 24°, allowing precise light control. Phase-cut dimming enables stepless adjustment of the light intensity. With a product length of 18.5 cm, a diameter of 8.5 cm, and a height of 16.5 cm, the luminaire is compactly designed. The IP20 protection rating classifies it as suitable for dry indoor areas. The declared service life is 50,000 hours.



Light source

2093861	A G D

Item no.	1004202
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	78
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	78.0
Number of luminaires at LS C16A	78.0
Level of inrush current	10 A
Duration of inrush current	50 µs
Beam angle	24°
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	18.5 cm
Height	16.5 cm
Diameter	8.5 cm

Accessories

1006168	NUMINOS® M, white front ring
1008145	NUMINOS® M, front ring, matt gold
1008141	NUMINOS® M, front ring, matt copper