NUMINOS® M | CL, PHASE

NUMINOS® M CL, PHASE, Surface-mounted ceiling light, 4000 K, 14 Watt, trailing edge, 36°, matt black

The NUMINOS® M SPOT is a surface-mounted ceiling luminaire characterised by its cylindrical shape and a matte black finish. It is designed for indoor use and is particularly suitable for accent lighting with a luminous flux of 1950 lumens and a colour temperature of 4000 K. The luminaire features a beam angle of 36° and phase-cut dimming, allowing for stepless light adjustment. The housing is made of aluminium combined with polycarbonate elements and measures 18.5 cm in length, 8.5 cm in diameter, and 16.5 cm in height. The IP20 protection rating permits use in protected indoor areas. The luminaire is equipped with a round canopy and offers a declared lifetime of 50,000 hours.



Light source

2093757	A G D

Item no.	1004211
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	78
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	78.0
Number of luminaires at LS C16A	78.0
Level of inrush current	10 A
Duration of inrush current	50 µs
Beam angle	36°
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	18.5 cm
Height	16.5 cm
Diameter	8.5 cm

Accessories

1006168	NUMINOS® M, white front ring
1008145	NUMINOS® M, front ring, matt gold
1008141	NUMINOS® M, front ring, matt copper