




NUMINOS® M | CL, PHASE

NUMINOS® M CL, PHASE, Surface-mounted ceiling light, 2700 K, 14 Watt, trailing edge, 24°, matt black

The NUMINOS® M CL, PHASE is a cylindrical surface-mounted ceiling luminaire suitable for indoor use. It features a colour temperature of 2700 K and delivers a luminous flux of 1750 lumens with a power consumption of 14 watts. The luminaire is equipped with a phase-cut dimming function, allowing for stepless brightness adjustment. The housing is matt black with a diameter of 8.5 cm and a height of 18.5 cm. The light distribution is provided with a beam angle of 24 degrees. The IP20 protection rating safeguards the luminaire against contact and solid foreign objects larger than 12.5 mm. With a lifespan of 50,000 hours, the luminaire is designed for long-lasting use.



Light source

2093865



Item no.	1004218
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	78
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	78.0
Number of luminaires at LS C16A	78.0
Level of inrush current	10 A
Duration of inrush current	50 µs
Beam angle	24°
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Height	18.5 cm
Diameter	8.5 cm
Net weight	0.69 kg

Accessories

1006168	NUMINOS® M, white front ring
1008145	NUMINOS® M, front ring, matt gold
1008141	NUMINOS® M, front ring, matt copper