




NUMINOS® M | CL, PHASE

NUMINOS® M CL, PHASE, Surface-mounted ceiling light, 2700 K, 14 Watt, trailing edge, 36°, matt white / matt black

The NUMINOS® M CL, PHASE is a cylindrical surface-mounted ceiling luminaire suitable for indoor use. It delivers a luminous flux of 1750 lumens at a colour temperature of 2700 K with a beam angle of 36°. The luminaire has a power consumption of 14 watts and features phase-cut dimming for stepless brightness control. The housing is available in matt white or matt black, with a diameter of 8.5 cm and a height of 18.5 cm. The IP20 rating indicates protection against solid foreign objects over 12.5 mm, but no protection against water. The declared service life is 50,000 hours.



Light source

2093865



Item no.	1004223
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	78
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	78.0
Number of luminaires at LS C16A	78.0
Level of inrush current	10 A
Duration of inrush current	50 µs
Beam angle	36°
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Height	18.5 cm
Diameter	8.5 cm
Net weight	0.69 kg

Accessories

1006168	NUMINOS® M, white front ring
1008145	NUMINOS® M, front ring, matt gold
1008141	NUMINOS® M, front ring, matt copper