




## NUMINOS® M | CL, PHASE

**NUMINOS® M CL, PHASE, Surface-mounted ceiling light, 4000 K, 14 Watt, trailing edge, 24°, matt white / matt black**

The surface-mounted ceiling luminaire NUMINOS® M CL, PHASE is designed for indoor use and features a cylindrical design. It is equipped with phase-cut dimming, allowing flexible brightness control. With a luminous flux of 1950 lumens at 14 watts and a colour temperature of 4000 K, the luminaire emits neutral white light with a beam angle of 24°. The housing is finished in matt white or matt black and has an IP20 rating, making it suitable for dust-protected indoor areas. The luminaire measures 8.5 cm in diameter and 18.5 cm in height. It is intended for ceiling surface mounting and offers a long service life of up to 50,000 hours.



### Light source

2093757



|                                   |                    |
|-----------------------------------|--------------------|
| Item no.                          | 1004238            |
| Lamps included                    | No                 |
| Number of different light outlets | 1                  |
| IP Code                           | IP20               |
| Assembly                          | Surface            |
| Assembly details                  | Ceiling,           |
| Dimmable                          | true               |
| Dimming technology                | trailing edge      |
| Number of through-wires           | 78                 |
| Primary nominal voltage           | 220-240V ~ 50/60Hz |
| Secondary power / voltage         | 350 mA             |
| Safety class                      | I                  |
| Wattage                           | 14 W               |
| Minimum ambient temperature       | -20°C              |
| Maximum ambient temperature       | 45°C               |
| Number of luminaires at LS B16A   | 78.0               |
| Number of luminaires at LS C16A   | 78.0               |
| Level of inrush current           | 10 A               |
| Duration of inrush current        | 50 µs              |
| Beam angle                        | 24°                |
| Color                             | white              |
| CRI                               | 90                 |
| UGR ≤                             | 16                 |
| LXXBXX data                       | L90B10             |
| Service life                      | 50 000 h           |
| Risk Group                        | 1                  |
| Height                            | 18.5 cm            |
| Diameter                          | 8.5 cm             |
| Net weight                        | 0.69 kg            |

## Accessories

|         |                                     |
|---------|-------------------------------------|
| 1006168 | NUMINOS® M, white front ring        |
| 1008145 | NUMINOS® M, front ring, matt gold   |
| 1008141 | NUMINOS® M, front ring, matt copper |