




NUMINOS® PD PHASE M

Indoor LED pendant light black/black 3000K 60°

The NUMINOS light system from SLV skilfully combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® PD PHASE M, which impresses as a pendant light with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The pendant light has a power consumption of 20.1 watts, a luminous flux of 1880 lumens, a colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



Tekniske data

Item no.	1004252
Montering	Surface
Monterings detaljer	Ceiling,Ceiling with Acc.
Dæmpbar	Ja
Dæmpningstype	trailing edge
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	500mA
IP Tæthedsgard	I
Watt	20.1 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	30 °C
Lumen	1880 lm
Farvetemperatur	3000 Kelvin
Spredningsvinkel	60 °
Farve	matt black
CRI	90
UGR ≤	22
LXXBXX-data	L80B50
Højde	18.5 cm
Diameter	8.5 cm
Pendellængde	250 cm
Nettovægt	0.979 kg

Lyskilde

791822	
--------	---

Tilbehør

1006168	NUMINOS® M , white front ring
---------	-------------------------------

Bruttovægt	1.198 kg
------------	----------

BIG WHITE side	108
----------------	-----