



NUMINOS® CL PHASE L

Indoor LED surface ceiling light white/black 2700K 60°

The NUMINOS light system from SLV perfectly combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® CL PHASE L indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2475 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

| | |
|---------------------------------|-------------------|
| Item no. | 1004320 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 700 mA |
| Safety class | I |
| Wattage | 28 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 30 °C |
| Number of luminaires at LS B16A | 34 |
| Number of luminaires at LS C16A | 58 |
| Level of inrush current | 6 A |
| Duration of inrush current | 40 µs |
| Lumen | 2475 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 60 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |

Light Source

| | |
|--------|---|
| 791800 |  |
|--------|---|

Accessories

| | |
|---------|-------------------------------|
| 1006169 | NUMINOS® L , white front ring |
|---------|-------------------------------|

| | |
|--------------------|----------------------|
| Service life | 50000 h |
| Light distribution | rotational symmetric |
| Light outlet | direct |
| Risk Group | 1 |
| Height | 21.3 cm |
| Diameter | 10 cm |
| Net weight | 0.95 kg |
| Gross weight | 1.26 kg |
| BIG WHITE Page | 105 |