



## NUMINOS® CL PHASE L

Indoor LED surface ceiling light black/black 4000K 60°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The different downlights and spotlights make a thousand lighting design options possible. Like with the NUMINOS® CL PHASE L indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2715 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

## TECHNICAL DATA

Item no.	1004332
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	34
Number of luminaires at LS C16A	58
Level of inrush current	6 A
Duration of inrush current	40 µs
Lumen	2715 lm
Colour temperature	4000 Kelvin
Beam angle	60 °
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B50

## Light Source

791825	
--------	---

## Accessories

1006169	NUMINOS® L , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	21.3 cm
Diameter	10 cm
Net weight	0.95 kg
Gross weight	1.26 kg
BIG WHITE Page	105