



## 3~ NUMINOS® DALI S

3 phase system light black/black 2700K 24°

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. Like with the 3~ NUMINOS® DALI S 3-phase system light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 985 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

## TECHNICAL DATA

|                                 |                           |
|---------------------------------|---------------------------|
| Item no.                        | 1004362                   |
| Rotating or tilting             | rotary Bar and tiltable   |
| Assembly details                | Track Ceiling, Track Wall |
| Dimmable                        | Yes                       |
| Dimming technology              | DALI                      |
| Primary nominal voltage         | 220-240V ~50/60Hz         |
| Secondary power / voltage       | 250 mA                    |
| Safety class                    | I                         |
| Wattage                         | 10.42 W                   |
| Minimum ambient temperature     | -20 °C                    |
| Maximum ambient temperature     | 40 °C                     |
| Number of luminaires at LS B16A | 72                        |
| Number of luminaires at LS C16A | 122                       |
| Level of inrush current         | 52 A                      |
| Duration of inrush current      | 1 µs                      |
| Lumen                           | 985 lm                    |
| Colour temperature              | 2700 Kelvin               |
| Beam angle                      | 24 °                      |
| Color                           | black                     |
| CRI                             | 90                        |
| UGR ≤                           | 16                        |
| LXXBXX data                     | L80B50                    |

## Light Source

|        |   |
|--------|---|
| 791819 |  |
|--------|---|

## Accessories

|         |                               |
|---------|-------------------------------|
| 1006167 | NUMINOS® S , white front ring |
|---------|-------------------------------|

|                    |                      |
|--------------------|----------------------|
| Service life       | 50000 h              |
| Light distribution | rotational symmetric |
| Light outlet       | direct               |
| Risk Group         | 1                    |
| Length             | 16.2 cm              |
| Height             | 14.5 cm              |
| Diameter           | 6.5 cm               |
| Net weight         | 0.56 kg              |
| Gross weight       | 0.85 kg              |
| BIG WHITE Page     | 112                  |