




## NUMINOS® SPOT DALI S

Indoor LED recessed ceiling light white/black 2700K 36°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® SPOT DALI S indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 985 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?



## TECHNICAL DATA

|                                 |                         |
|---------------------------------|-------------------------|
| Item no.                        | 1004391                 |
| Rotating or tilting             | rotary Bar and tiltable |
| Assembly                        | Surface                 |
| Assembly details                | Ceiling,Wall            |
| Dimmable                        | Yes                     |
| Dimming technology              | DALI                    |
| Primary nominal voltage         | 220-240V ~50/60Hz       |
| Secondary power / voltage       | 250 mA                  |
| Safety class                    | I                       |
| Wattage                         | 10.42 W                 |
| Minimum ambient temperature     | -20 °C                  |
| Maximum ambient temperature     | 40 °C                   |
| Number of luminaires at LS B16A | 72                      |
| Number of luminaires at LS C16A | 122                     |
| Level of inrush current         | 52 A                    |
| Duration of inrush current      | 1 µs                    |
| Lumen                           | 985 lm                  |
| Colour temperature              | 2700 Kelvin             |
| Beam angle                      | 36 °                    |
| Color                           | white                   |
| CRI                             | 90                      |
| UGR ≤                           | 16                      |

## Light Source

|        |   |
|--------|---|
| 791819 |  |
|--------|---|

## Accessories

|         |                               |
|---------|-------------------------------|
| 1006167 | NUMINOS® S , white front ring |
|---------|-------------------------------|

|                    |                      |
|--------------------|----------------------|
| LXXBXX data        | L80B50               |
| Service life       | 50000 h              |
| Light distribution | rotational symmetric |
| Light outlet       | direct               |
| Risk Group         | 1                    |
| Length             | 16.2 cm              |
| Height             | 14.5 cm              |
| Diameter           | 6.5 cm               |
| Net weight         | 0.66 kg              |
| Gross weight       | 0.95 kg              |
| BIG WHITE Page     | 100                  |