




NUMINOS® S | WL, DALI

NUMINOS® S CW, DALI, Surface-mounted ceiling light, 3000 K, 7.8 Watt, DALI, 24°, matt white / matt black

The NUMINOS® S is a cylindrical surface-mounted ceiling luminaire suitable for indoor use. It is equipped with a light source that offers a colour temperature of 3000 K and a beam angle of 24°, enabling directional lighting. The luminaire has a power consumption of 7.8 W and produces a luminous flux of 1050 lumens. The housing is made of aluminium and polycarbonate, with a ROUND canopy design. The luminaire features DALI 2 and touch dimming functions, allowing flexible light control. With an IP20 rating, it is suitable for use in dry indoor environments. The dimensions are 16.2 cm in length, 6.5 cm in diameter, and 14.5 cm in height. This luminaire is part of the NUMINOS® product line and is ideal for applications requiring a compact, high-performance surface-mounted ceiling light.



Light source

2093856



Item no.	1004398
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	166
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	200 mA
Safety class	I
Wattage	8 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	166.0
Number of luminaires at LS C16A	187.0
Level of inrush current	2.43 A
Duration of inrush current	202 µs
Beam angle	24°
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	16.2 cm
Height	14.5 cm
Diameter	6.5 cm

Accessories

1006167	NUMINOS® S, white front ring
1008144	NUMINOS® S, front ring, matt gold
1008140	NUMINOS® S, front ring, matt copper