




## **NUMINOS® SPOT DALIS**

Indoor LED recessed ceiling light white/black 4000K  $24^{\circ}$ 

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Like with the NUMINOS® SPOT DALI S indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. The spotlight is perfect for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1100 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



## **TECHNICAL DATA**

Item no.	1004406
Rotating or tilting	rotary Bar and tiltable
Assembly	Surface
Assembly details	Ceiling, Wall
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10.42 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	72
Number of luminaires at LS C16A	122
Level of inrush current	52 A
Duration of inrush current	1 μs
Lumen	1100 lm
Colour temperature	4000 Kelvin
Beam angle	24°
Color	white
CRI	90
UGR≤	16



## **Light Source**

791831	A E	
Accessories		
1006167	NUMINOS® S , white front ring	

LXXBXX data  L80B50  Service life  50000 h  Light distribution  rotational symmetric  direct  Risk Group  1  Length  16.2 cm  Height  14.5 cm  Diameter  6.5 cm  Net weight  0.66 kg  Gross weight  0.95 kg  BIG WHITE Page		
Light distribution       rotational symmetric         Light outlet       direct         Risk Group       1         Length       16.2 cm         Height       14.5 cm         Diameter       6.5 cm         Net weight       0.66 kg         Gross weight       0.95 kg	LXXBXX data	L80B50
Light outlet         direct           Risk Group         1           Length         16.2 cm           Height         14.5 cm           Diameter         6.5 cm           Net weight         0.66 kg           Gross weight         0.95 kg	Service life	50000 h
Risk Group         1           Length         16.2 cm           Height         14.5 cm           Diameter         6.5 cm           Net weight         0.66 kg           Gross weight         0.95 kg	Light distribution	rotational symmetric
Length       16.2 cm         Height       14.5 cm         Diameter       6.5 cm         Net weight       0.66 kg         Gross weight       0.95 kg	Light outlet	direct
Height 14.5 cm  Diameter 6.5 cm  Net weight 0.66 kg  Gross weight 0.95 kg	Risk Group	1
Diameter 6.5 cm  Net weight 0.66 kg  Gross weight 0.95 kg	Length	16.2 cm
Net weight 0.66 kg  Gross weight 0.95 kg	Height	14.5 cm
Gross weight 0.95 kg	Diameter	6.5 cm
	Net weight	0.66 kg
BIG WHITE Page 100	Gross weight	0.95 kg
	BIG WHITE Page	100