NUMINOS® S | CL, DALI

NUMINOS® S CL, DALI, Surface-mounted ceiling light, 3000 K, 7.8 Watt, DALI, 24°, matt white / matt black

The NUMINOS® S CL is a ceiling surface-mounted luminaire with a cylindrical design, suitable for indoor use. It offers a luminous flux of 1050 lumens at a colour temperature of 3000 K and a beam angle of 24°. The luminaire is equipped with DALI 2 and touch dimming functions, enabling flexible light control. The housing is made of aluminium and is available in matt white or matt black. With a diameter of 6.5 cm and a height of 16.2 cm, the luminaire is compactly designed. The IP20 protection rating allows use in dry indoor environments. The declared lifetime is 50,000 hours.



Light source

2093856	A G D

Item no.	1004422
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	166
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	200 mA
Safety class	I
Wattage	8 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	166.0
Number of luminaires at LS C16A	187.0
Level of inrush current	2.43 A
Duration of inrush current	202 µs
Beam angle	24°
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Height	16.2 cm
Diameter	6.5 cm
Net weight	0.48 kg

Accessories

1006167	NUMINOS® S, white front ring
1008144	NUMINOS® S, front ring, matt gold
1008140	NUMINOS® S, front ring, matt copper