


NUMINOS® M | 3Ph., DALI

NUMINOS® M 3Ph., DALI, 3~ Spotlight, cylindrical, 2700 K, 13 Watt, DALI, 60°, matt white / matt black

The NUMINOS® M 3Ph. DALI 3~ Spot is a cylindrically shaped spotlight designed for mounting on ceiling track systems. It is suitable for indoor use, for example in exhibition rooms, offices, or retail spaces. The spot delivers a luminous flux of 1750 lumens at a colour temperature of 2700 Kelvin with a beam angle of 60°. The light source has a power consumption of 13 watts and a declared lifetime of 50,000 hours. The housing is made of aluminium and is available in matt white or matt black. The spotlight features DALI-2 and touch dimming functions and offers an IP20 protection rating. With a length of 18.5 cm, a diameter of 8.5 cm, and a height of 16.5 cm, it is compact and versatile.



Light source

2093865	A D

Item no.	1004464
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Track
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	94.0
Number of luminaires at LS C16A	94.0
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Beam angle	60°
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	18.5 cm
Height	16.5 cm
Diameter	8.5 cm
Net weight	0.83 kg

Accessories

1006168	NUMINOS® M, white front ring
1008145	NUMINOS® M, front ring, matt gold
1008141	NUMINOS® M, front ring, matt copper