



## 3~ NUMINOS® DALI M

### 3 phase system light black/black 3000K 24°

The NUMINOS light system from SLV perfectly combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. Like with the 3~ NUMINOS® DALI M 3-phase system light LED, which impresses with its high-quality workmanship and light. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1955 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

## TECHNICAL DATA

Item no.	1004466
Rotating or tilting	rotary Bar and tiltable
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20.1 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	8
Number of luminaires at LS C16A	16
Level of inrush current	10 A
Duration of inrush current	30 µs
Lumen	1955 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L80B50

## Light Source

791822	
--------	---

## Accessories

1006168	NUMINOS® M , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	18.5 cm
Height	16.5 cm
Diameter	8.5 cm
Net weight	0.83 kg
Gross weight	1.13 kg
BIG WHITE Page	112