




NUMINOS® M | CL, DALI

NUMINOS® M CL, DALI, Surface-mounted ceiling light, 3000 K, 13 Watt, DALI, 60°, matt white / matt black

The NUMINOS® M SPOT is a surface-mounted ceiling luminaire designed for indoor use. It features a cylindrical shape and is available in a matt white or matt black finish. With a colour temperature of 3000 K, it emits warm white light. The luminaire operates at a power of 13 watts and provides a luminous flux of 1800 lumens with a beam angle of 60 degrees. The housing is made of aluminium, while the diffuser is manufactured from polycarbonate. The luminaire is equipped with a DALI-2 dimming function, allowing for flexible light control. The IP20 rating indicates protection against solid foreign objects larger than 12.5 mm, but no protection against water. With a product length of 18.5 cm, a diameter of 8.5 cm, and a height of 16.5 cm, the luminaire is compactly sized. It is particularly suitable for use in residential and commercial spaces where directed, dimmable lighting is required.



Light source

2093861



Item no.	1004496
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	94
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	94.0
Number of luminaires at LS C16A	94.0
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Beam angle	60°
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	18.5 cm
Height	16.5 cm
Diameter	8.5 cm

Accessories

1006168	NUMINOS® M, white front ring
1008145	NUMINOS® M, front ring, matt gold
1008141	NUMINOS® M, front ring, matt copper