


NUMINOS® M | CL, DALI

NUMINOS® M CL, DALI, Surface-mounted ceiling light, 2700 K, 13 Watt, DALI, 60°, matt white / matt black

The NUMINOS® M CL is a surface-mounted ceiling luminaire with a cylindrical housing, suitable for indoor use. It delivers a luminous flux of 1750 lumens at a colour temperature of 2700 K and a beam angle of 60°. The luminaire features DALI-2 and touch dimming, allowing flexible light control. The housing is made of aluminium and is available in matt white or matt black. With a diameter of 8.5 cm and a height of 18.5 cm, it offers a compact design. Its IP20 protection rating makes it suitable for protected indoor areas. The luminaire has a declared lifetime of 50,000 hours.



Light source

2093865	A to G D

Item no.	1004512
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	94
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	94.0
Number of luminaires at LS C16A	94.0
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Beam angle	60°
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Height	18.5 cm
Diameter	8.5 cm
Net weight	0.73 kg

Accessories

1006168	NUMINOS® M, white front ring
1008145	NUMINOS® M, front ring, matt gold
1008141	NUMINOS® M, front ring, matt copper