




## NUMINOS® PD DALI M

Indoor LED pendant light black/black 4000K 24°

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® PD DALI M pendant light, which impresses with its high-quality workmanship and light. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The pendant light can convince with a power consumption of 20.1 watts, luminous flux of 2125 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

|                                 |                           |
|---------------------------------|---------------------------|
| Item no.                        | 1004546                   |
| Assembly                        | Surface                   |
| Assembly details                | Ceiling,Ceiling with Acc. |
| Dimmable                        | Yes                       |
| Dimming technology              | DALI                      |
| Primary nominal voltage         | 220-240V ~50/60Hz         |
| Secondary power / voltage       | 500 mA                    |
| Safety class                    | I                         |
| Wattage                         | 20.1 W                    |
| Minimum ambient temperature     | -20 °C                    |
| Maximum ambient temperature     | 30 °C                     |
| Number of luminaires at LS B16A | 8                         |
| Number of luminaires at LS C16A | 16                        |
| Level of inrush current         | 10 A                      |
| Duration of inrush current      | 30 µs                     |
| Lumen                           | 2125 lm                   |
| Colour temperature              | 4000 Kelvin               |
| Beam angle                      | 24 °                      |
| Color                           | black                     |
| CRI                             | 90                        |
| UGR ≤                           | 19                        |
| LXXBXX data                     | L80B50                    |

## Light Source

|        |   |
|--------|---|
| 791825 |  |
|--------|---|

## Accessories

|         |                               |
|---------|-------------------------------|
| 1006168 | NUMINOS® M , white front ring |
|---------|-------------------------------|

|                    |                      |
|--------------------|----------------------|
| Service life       | 50000 h              |
| Light distribution | rotational symmetric |
| Light outlet       | direct               |
| Risk Group         | 1                    |
| Height             | 18.5 cm              |
| Diameter           | 8.5 cm               |
| Pendant length     | 250 cm               |
| Net weight         | 1.25 kg              |
| Gross weight       | 1.4 kg               |
| BIG WHITE Page     | 108                  |