NUMINOS® L | CL, DALI

NUMINOS® L CL, DALI, Surface-mounted ceiling light, 2700 K, 19 Watt, DALI, 24°, matt black

The NUMINOS® L SPOT is a surface-mounted ceiling luminaire with a cylindrical design, suitable for indoor use. It delivers a luminous flux of 2300 lumens at a colour temperature of 2700 K and a beam angle of 24°. The luminaire features a DALI 2 dimming function as well as touch control, allowing for flexible light adjustment. The housing is made of aluminium and polycarbonate, ensuring a robust construction. With dimensions of 21.3 cm in length, 10 cm in diameter, and 18 cm in height, the luminaire is compactly designed. The IP20 rating makes it suitable for dry indoor environments. The NUMINOS® L SPOT is designed for professional applications and offers a declared service life of 50,000 hours.



Light source

2093865	A G D

Item no.	1004578
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	94
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	94.0
Number of luminaires at LS C16A	94.0
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Beam angle	24°
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	21.3 cm
Height	18 cm
Diameter	10 cm

Accessories

1006169	NUMINOS® L, white front ring
1008146	NUMINOS® L, front ring, matt gold
1008142	NUMINOS® L, front ring, matt copper