NUMINOS® L | CL, DALI

NUMINOS® L CL, DALI, Surface-mounted ceiling light, 2700 K, 19 Watt, DALI, 60°, matt black

The NUMINOS® L SPOT is a ceiling surface-mounted luminaire with a cylindrical shape, suitable for indoor use. It delivers a luminous flux of 2300 lumens at a colour temperature of 2700 K and a beam angle of 60°. The luminaire features DALI 2 dimming and touch control, allowing flexible adjustment of the light intensity. The housing is made of aluminium and polycarbonate, ensuring a robust construction. With a diameter of 10 cm, a length of 21.3 cm, and a height of 18 cm, it is compactly sized. The IP20 protection rating offers protection against solid foreign objects with a diameter of 12.5 mm and above. The luminaire is suitable for use in residential and work areas where directed and dimmable lighting is desired.



Light source

2093865	A G D

Item no.	1004580
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	94
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	94.0
Number of luminaires at LS C16A	94.0
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Beam angle	60°
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	21.3 cm
Height	18 cm
Diameter	10 cm

Accessories

1006169	NUMINOS® L, white front ring
1008146	NUMINOS® L, front ring, matt gold
1008142	NUMINOS® L, front ring, matt copper