NUMINOS® L | CL, DALI

NUMINOS® L CL, DALI, Surface-mounted ceiling light, 3000 K, 19 Watt, DALI, 24°, matt black

The NUMINOS® L SPOT is a surface-mounted ceiling luminaire suitable for indoor use. It features a cylindrical shape and is typically installed in areas where targeted accent lighting is desired. The luminaire is equipped with LED technology, providing a luminous flux of 2400 lumens at a colour temperature of 3000 Kelvin. The beam angle is 24 degrees, enabling directed light distribution. The housing is made of aluminium and polycarbonate, ensuring a robust construction. Installation is carried out directly on the ceiling. The luminaire is equipped with DALI 2 and touch dimming, allowing flexible light control. The protection rating is IP20, making it suitable for use in dry indoor environments. With a declared service life of 50,000 hours, it is designed for long-lasting operation.



Light source

2093861	A G D

Item no.	1004586
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	94
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	94.0
Number of luminaires at LS C16A	94.0
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Beam angle	24°
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	21.3 cm
Height	18 cm
Diameter	10 cm

Accessories

1006169	NUMINOS® L, white front ring
1008146	NUMINOS® L, front ring, matt gold
1008142	NUMINOS® L, front ring, matt copper