NUMINOS® L | CL, DALI

NUMINOS® L CL, DALI, Surface-mounted ceiling light, 3000 K, 19 Watt, DALI, 36°, matt black

The NUMINOS® L SPOT is a surface-mounted ceiling luminaire, particularly suitable for indoor use. It features a cylindrical shape and comes in a matt black housing made of aluminium and polycarbonate. With a light output of 2400 lumens at 19 watts, the luminaire produces warm white light at 3000 Kelvin with a beam angle of 36 degrees. Control is via DALI 2 and touch dimming, allowing for flexible light management. The luminaire has a round canopy and measures 21.3 cm in length, 10 cm in diameter, and 18 cm in height. It has an IP20 rating, making it suitable for use in dry indoor environments. The declared service life is 50,000 hours.



Light source

2093861	A G D

Item no.	1004587
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	94
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	94.0
Number of luminaires at LS C16A	94.0
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Beam angle	36°
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	21.3 cm
Height	18 cm
Diameter	10 cm

Accessories

1006169	NUMINOS® L, white front ring
1008146	NUMINOS® L, front ring, matt gold
1008142	NUMINOS® L, front ring, matt copper