




NUMINOS® L | CL, DALI

NUMINOS® L CL, DALI, Surface-mounted ceiling light, 3000 K, 19 Watt, DALI, 60°, matt black

The NUMINOS® L SPOT is a surface-mounted ceiling luminaire suitable for indoor use. It features a cylindrical shape and is equipped with a 19-watt light source with a colour temperature of 3000 Kelvin, producing directional light with a beam angle of 60°. The luminaire delivers a luminous flux of 2400 lumens and includes DALI 2 dimming as well as touch control, enabling flexible light management. The housing is made of aluminium and polycarbonate, ensuring a robust construction. With a diameter of 10 cm, a length of 21.3 cm, and a height of 18 cm, the luminaire is compactly designed. The IP20 rating makes it suitable for dry indoor areas. The round shape of the canopy facilitates easy ceiling installation.



Light source

2093861



Item no.	1004588
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	94
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	94.0
Number of luminaires at LS C16A	94.0
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Beam angle	60°
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	21.3 cm
Height	18 cm
Diameter	10 cm

Accessories

1006169	NUMINOS® L, white front ring
1008146	NUMINOS® L, front ring, matt gold
1008142	NUMINOS® L, front ring, matt copper