




NUMINOS® L | CL, DALI

NUMINOS® L CL, DALI, Surface-mounted ceiling light, 4000 K, 19 Watt, DALI, 24°, matt black

The NUMINOS® L SPOT is a surface-mounted ceiling luminaire distinguished by its cylindrical design and matte black finish. It is designed for indoor use and is particularly suitable for targeted, directional lighting. The luminaire provides a luminous flux of 2600 lumens at 19 watts and a colour temperature of 4000 K, producing neutral white light. The beam angle is 24°, allowing for precise light distribution. The housing is made of aluminium and polycarbonate, ensuring a robust construction. With a height of 18 cm and a diameter of 10 cm, the luminaire is compactly sized. Control is via DALI 2 and touch technology. The IP20 protection rating permits use in protected indoor areas.



Light source

2093757



Item no.	1004594
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	94
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	94.0
Number of luminaires at LS C16A	94.0
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Beam angle	24°
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	21.3 cm
Height	18 cm
Diameter	10 cm

Accessories

1006169	NUMINOS® L, white front ring
1008146	NUMINOS® L, front ring, matt gold
1008142	NUMINOS® L, front ring, matt copper