




NUMINOS® L | CL, DALI

NUMINOS® L CL, DALI, Surface-mounted ceiling light, 2700 K, 19 Watt, DALI, 36°, matt white / matt black

The NUMINOS® L CL is a cylindrical surface-mounted ceiling light suitable for indoor use. It delivers a luminous flux of 2300 lumens with a colour temperature of 2700 K and a beam angle of 36°. The luminaire features DALI 2 and touch dimming, allowing for flexible light control. The housing is made of aluminium and is available in matt white or matt black. With a diameter of 10 cm and a height of 21.3 cm, the luminaire can be installed space-efficiently. The IP20 protection rating provides basic protection against contact and solid foreign objects. The NUMINOS® L CL is designed for demanding lighting tasks and impresses with a long service life of 50,000 hours.



Light source

2093865



Item no.	1004607
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	94
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	94.0
Number of luminaires at LS C16A	94.0
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Beam angle	36°
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Height	21.3 cm
Diameter	10 cm
Net weight	1.04 kg

Accessories

1006169	NUMINOS® L, white front ring
1008146	NUMINOS® L, front ring, matt gold
1008142	NUMINOS® L, front ring, matt copper