




NUMINOS® L | CL, DALI

NUMINOS® L CL, DALI, Surface-mounted ceiling light, 2700 K, 19 Watt, DALI, 60°, matt white / matt black

The NUMINOS® L CL is a cylindrical surface-mounted ceiling luminaire suitable for indoor installation. It offers a luminous flux of 2300 lumens with a colour temperature of 2700 K and a beam angle of 60°. The luminaire features DALI-2 and touch dimming functions, allowing for flexible light control. The housing is made of aluminium and is available in matt white or matt black. With a height of 21.3 cm and a diameter of 10 cm, the luminaire integrates unobtrusively into various interior designs. The IP20 protection rating indicates that the luminaire is intended for use in dry indoor environments. The declared service life is 50,000 hours.



Light source

2093865



Item no.	1004608
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	94
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	94.0
Number of luminaires at LS C16A	94.0
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Beam angle	60°
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Height	21.3 cm
Diameter	10 cm
Net weight	1.04 kg

Accessories

1006169	NUMINOS® L, white front ring
1008146	NUMINOS® L, front ring, matt gold
1008142	NUMINOS® L, front ring, matt copper