




NUMINOS® L | CL, DALI

NUMINOS® L CL, DALI, Surface-mounted ceiling light, 3000 K, 19 Watt, DALI, 36°, matt black

The NUMINOS® L CL is a ceiling-mounted luminaire with a cylindrical design, suitable for indoor use. It delivers a light output of 2400 lumens at a power consumption of 19 watts and emits warm white light at 3000 Kelvin. The luminaire features DALI 2 and touch dimming functions, allowing for flexible light control. The housing is made of aluminium with a matt black finish. With a diameter of 10 cm and a height of 21.3 cm, the luminaire is compactly designed. The beam angle is 36 degrees, directing the light precisely. The IP20 protection rating indicates that the luminaire is suitable for use in dry indoor environments. The declared service life is 50,000 hours.



Light source

2093861



Item no.	1004611
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	94
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	94.0
Number of luminaires at LS C16A	94.0
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Beam angle	36°
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Height	21.3 cm
Diameter	10 cm
Net weight	1.04 kg

Accessories

1006169	NUMINOS® L, white front ring
1008146	NUMINOS® L, front ring, matt gold
1008142	NUMINOS® L, front ring, matt copper