




NUMINOS® L | CL, DALI

NUMINOS® L CL, DALI, Surface-mounted ceiling light, 4000 K, 19 Watt, DALI, 36°, matt black

The NUMINOS® L CL is a ceiling surface-mounted luminaire with a cylindrical design, suitable for indoor use. It delivers a luminous flux of 2600 lumens at a colour temperature of 4000 K and a beam angle of 36°. The luminaire features DALI 2 and touch dimming functions, allowing flexible control of light intensity. The housing is made of aluminium and finished in matte black. With a height of 21.3 cm and a diameter of 10 cm, it is compactly sized. The IP20 protection rating indicates that the luminaire is designed for use in dry indoor environments. The declared lifetime is 50,000 hours.



Light source

2093757



Item no.	1004619
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	94
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	94.0
Number of luminaires at LS C16A	94.0
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Beam angle	36°
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Height	21.3 cm
Diameter	10 cm
Net weight	1.04 kg

Accessories

1006169	NUMINOS® L, white front ring
1008146	NUMINOS® L, front ring, matt gold
1008142	NUMINOS® L, front ring, matt copper