




NUMINOS® L | CL, DALI

NUMINOS® L CL, DALI, Surface-mounted ceiling light, 4000 K, 19 Watt, DALI, 60°, matt black

The NUMINOS® L CL is a surface-mounted ceiling light with a cylindrical design, suitable for indoor use. It features a luminous flux of 2600 lumens at a colour temperature of 4000 K and a beam angle of 60°. The luminaire is equipped with durable LED technology and has a declared service life of 50,000 hours. The housing is made of aluminium with a matt black finish. Installation is carried out directly on the ceiling. The luminaire includes DALI 2 and touch dimming functions, allowing flexible light control. The protection rating is IP20, making it suitable for dust-protected indoor areas. With a height of 21.3 cm and a diameter of 10 cm, it offers compact dimensions for versatile applications.



Light source

2093757



Item no.	1004620
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	94
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	94.0
Number of luminaires at LS C16A	94.0
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Beam angle	60°
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Height	21.3 cm
Diameter	10 cm
Net weight	1.04 kg

Accessories

1006169	NUMINOS® L, white front ring
1008146	NUMINOS® L, front ring, matt gold
1008142	NUMINOS® L, front ring, matt copper