




NUMINOS® L | CL, DALI

NUMINOS® L CL, DALI, Surface-mounted ceiling light, 4000 K, 19 Watt, DALI, 24°, matt white / matt black

The NUMINOS® L CL is a ceiling surface-mounted luminaire with a cylindrical design, suitable for indoor use. It features a colour temperature of 4000 K and a luminous flux of 2600 lumens with an energy consumption of 19 watts. The luminaire is equipped with DALI 2 and touch dimming functions, allowing flexible light control. The housing is made of aluminium and is available in matt white and matt black. With a diameter of 10 cm and a height of 21.3 cm, the luminaire is compactly designed. The beam angle is 24°, supporting precise light distribution. The IP20 protection rating classifies it as suitable for indoor use. The declared service life is 50,000 hours.



Light source

2093757



Item no.	1004622
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	94
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	94.0
Number of luminaires at LS C16A	94.0
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Beam angle	24°
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Height	21.3 cm
Diameter	10 cm
Net weight	1.04 kg

Accessories

1006169	NUMINOS® L, white front ring
1008146	NUMINOS® L, front ring, matt gold
1008142	NUMINOS® L, front ring, matt copper