




## OCULUS CW

Indoor LED wall and ceiling mounted light white  
DIM-TO-WARM 2000-3000K

With a high colour rendering index (CRI>90) and the option of dim-to-warm dimming for an especially warm light (2000-3000K), every member of the OCULUS family can conjure up a unique lighting mood. The special lens optics provide a sharply contoured lighting effect, making this light perfect for accent lighting in sophisticated homes, medical practices, law firms, cafés, hotels and restaurants. By using the included frosted shade, the light can also be adjusted to provide diffuse light distribution rather than sharply contoured lighting.



### TECHNICAL DATA

Item no.	1004665
Number of different light outlets	1
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	Dim-to-Warm, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	11 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	13 A
Duration of inrush current	8 µs
Stroboscopic effect (SVM)	0.09
Lumen	36-780 lm
Colour temperature	2000-3000 Kelvin
Beam angle	100 °
Color	white
CRI	90

## Light Source

916608	
--------	---

<b>LXXBXX data</b>	L70B50
<b>Service life</b>	25000 h
<b>Light distribution</b>	rotational symmetric
<b>Light outlet</b>	direct
<b>Risk Group</b>	1
<b>Height</b>	18.5 cm
<b>Diameter</b>	11.5 cm
<b>Net weight</b>	1.2 kg
<b>Gross weight</b>	1.498 kg
<b>BIG WHITE Page</b>	399