




OCULUS UP/DOWN WL

Indoor LED wall-mounted light black 2000-3000K

With a high colour rendering index (CRI>90) and the option of dim-to-warm dimming for an especially warm light (2000-3000K), every member of the OCULUS family can conjure up a unique lighting mood. The special lens optics provide a sharply contoured lighting effect, making this light perfect for accent lighting in sophisticated homes, medical practices, law firms, cafés, hotels and restaurants. By using the included frosted shade, the light can also be adjusted to provide diffuse light distribution rather than sharply contoured lighting.



TECHNICAL DATA

Item no.	1004670
Number of different light outlets	2
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	Dim-to-Warm, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	15 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Level of inrush current	15 A
Duration of inrush current	10 µs
Stroboscopic effect (SVM)	0.02
Lumen	44-1110 lm
Colour temperature	2000-3000 Kelvin
Beam angle	100 °
Color	black

Light Source

916398	
--------	---

CRI	90
LXXBXX data	L70B50
Service life	25000 h
Light distribution	rotational symmetric
Light outlet	direct - indirect
Risk Group	1
Height	11 cm
Depth	12.5 cm
Diameter	9 cm
Net weight	0.864 kg
Gross weight	1.073 kg
BIG WHITE Page	355