




OCULUS PD

Indoor LED pendant light single white DIM-TO-WARM 2000-3000K

With a high colour rendering index (CRI>90) and the option of dim-to-warm dimming for an especially warm light (2000-3000K), every member of the OCULUS family can conjure up a unique lighting mood. The special lens optics provide a sharply contoured lighting effect, making this light perfect for accent lighting in sophisticated homes, medical practices, law firms, cafés, hotels and restaurants. By using the included frosted shade, the light can also be adjusted to provide diffuse light distribution rather than sharply contoured lighting.



TECHNICAL DATA

| | |
|-----------------------------------|---------------------------|
| Item no. | 1004673 |
| Number of different light outlets | 1 |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling,Pendant Profile |
| Dimmable | Yes |
| Dimming technology | Dim-to-Warm,trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 250 mA |
| Safety class | II |
| Wattage | 11 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 50 °C |
| Level of inrush current | 13 A |
| Duration of inrush current | 8 µs |
| Stroboscopic effect (SVM) | 0.09 |
| Lumen | 35,6-780 lm |
| Colour temperature | 2000-3000 Kelvin |
| Beam angle | 100 ° |
| Color | white |
| CRI | 90 |
| LXXBXX data | L70B50 |

Light Source

| | |
|--------|---|
| 916608 |  |
|--------|---|

| | |
|---------------------------|----------------------|
| Service life | 25000 h |
| Light distribution | rotational symmetric |
| Light outlet | direct |
| Risk Group | 1 |
| Height | 9 cm |
| Diameter | 9 cm |
| Pendant length | 250 cm |
| Net weight | 0.662 kg |
| Gross weight | 0.79 kg |
| BIG WHITE Page | 294 |