






OVALISK CL

LED Outdoor ceiling-mounted ceiling light anthracite CCT switch 3000/4000K

Genuine glass and a perfectly-shaped design with a playful touch thanks to the combination of different materials and shapes used: the lights of the OVALISK family are modern eye-catchers that will look at home in the outdoor area of any sophisticated home or restaurant. OVALISK doesn't just shine with its high-quality appearance - it will also win you over with its easy installation and variable light colour (3000/4000K), which can be selected via CCT switch. And thanks to a high IP protection rating of 65, OVALISK is also perfectly protected from the elements.




TECHNICAL DATA

| Item no. | 1004677 |
|-----------------------------|-------------------|
| IP Code | IP 65 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Surface |
| Assembly details | Ceiling |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 350 mA |
| Safety class | I |
| Wattage | 7.9 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 45 °C |
| Level of inrush current | 4.7 A |
| Duration of inrush current | 30 µs |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 540/570 lm |
| Colour temperature | 3000/4000 Kelvin |
| Color | anthracite |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 30000 h |
| Risk Group | 1 |
| | |



Light Source



| Height | 25.5 cm |
|----------------|----------|
| Diameter | 17 cm |
| Net weight | 2.081 kg |
| Gross weight | 3.075 kg |
| BIG WHITE Page | 797 |
| | |