




OVALISK 75 FL

Outdoor LED free-standing light anthracite CCT switch 3000/4000K

Genuine glass and a perfectly-shaped design with a playful touch thanks to the combination of different materials and shapes used: the lights of the OVALISK family are modern eye-catchers that will look at home in the outdoor area of any sophisticated home or restaurant. OVALISK doesn't just shine with its high-quality appearance - it will also win you over with its easy installation and variable light colour (3000/4000K), which can be selected via CCT switch. And thanks to a high IP protection rating of 65, OVALISK is also perfectly protected from the elements.



TECHNICAL DATA

Item no.	1004680
IP Code	IP 65
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ground
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	9.2 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Level of inrush current	4.7 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.01
Lumen	580/630 lm
Colour temperature	3000/4000 Kelvin
Color	anthracite
CRI	80
LXXBXX data	L70B50
Service life	30000 h
Risk Group	0

Light Source

916555	
--------	---

Accessories

228730	CONNECTION BOX , 3-pin, IP68
228712	CONCRETE ANCHOR , for garden lights
228722	EARTH SPIKE , for gar- den luminaires, galvanis- ed steel

Height	75 cm
Diameter	17 cm
Net weight	2.884 kg
Gross weight	4.877 kg
BIG WHITE Page	653