




3~ SIGHT MOVE DALI

3 phase system light white 4000K

The modern SIGHT wall and ceiling light is ideal for surface mounting or busbar. The powerful luminous flux of 3100 lumens and the low glare are just some of the arguments that make the 3-phase system light LED the ideal basic lighting solution. The light made of aluminium and polymethylacrylate (PMMA) in the colour white and frosted cuts a professional figure everywhere. With its LED lifespan of 30,000 hours, SIGHT is also extremely sustainable. Experience SIGHT in action and convince yourself of a successful lighting experience.



TECHNICAL DATA

Item no.	1004693
Number of different light outlets	1
Rotating or tilting	tiltable
IP Code	IP20
Assembly details	Track Ceiling,Track Wall
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	26 W
Minimum ambient temperature	-30 °C
Maximum ambient temperature	40 °C
Rated standby power	0.29 W
Number of luminaires at LS B16A	43
Number of luminaires at LS C16A	63
Stroboscopic effect (SVM)	0
Lumen	3100 lm
Colour temperature	4000 Kelvin
Beam angle	75 °
Color	white
CRI	90

Light Source

916344	
--------	---

UGR \leq	25
LXXBXX data	L90B20
Service life	50000 h
Light outlet	direct
Risk Group	1
Length	45 cm
Width	5.6 cm
Height	10.5 cm
Net weight	1.24 kg
Gross weight	1.327 kg
BIG WHITE Page	533