




PANEL TRACK round 200mm

1-phase spot, white, 18W 3000K

Modern and space-saving at the same time, PANEL provides efficient basic lighting. A pleasant, homogeneous and glare-free light is produced by the 1-phase system light LED with 1,800 lumen and 3,000 Kelvin. Made of polycarbonate (PC) and steel, it is also extremely sustainable with an LED lifespan of 50,000 hours. When will you test out the benefits of SLV's impressive indoor lights?



TECHNICAL DATA

Item no.	1004936
Number of different light outlets	1
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Impact resistance	0.2 Joule
Assembly details	Track Ceiling, Track Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	450 mA
Safety class	II
Wattage	18 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	15 A
Duration of inrush current	20 µs
Stroboscopic effect (SVM)	0.01
Lumen	1800 lm
Colour temperature	3000 Kelvin
Color	white
CRI	90
LXXBXX data	L70B50
Service life	50000 h
Light distribution	rotational symmetric

Light Source

916407	
--------	---

Light outlet	direct
Risk Group	1
Length	23.1 cm
Width	20 cm
Height	11.05 cm
Net weight	0.453 kg
Gross weight	0.615 kg
BIG WHITE Page	507