



NUMINOS® MOVE S

black recessed ceiling light, 4000K 55°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you provide a thousand lighting design possibilities. Also with the NUMINOS® MOVE S recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. This means that easy installation is a mere formality. When will you choose SLV's modular variety?

TECHNICAL DATA

| | |
|-----------------------------------|-------------------------|
| Item no. | 1005361 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary bar and tiltable |
| IP Code | IP 20 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 250 mA |
| Safety class | III |
| Wattage | 8.6 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 730 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 55 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 1 |

Light Source

| | |
|--------|---|
| 791831 |  |
|--------|---|

Accessories

| | |
|---------|--|
| 1006458 | LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004789 | NUMINOS® S , diffuser Wabe |
| 1004067 | LED driver , 15W 250mA DALI |
| 1004788 | NUMINOS® S , diffuser Frosted |
| 1004787 | NUMINOS® S , diffuser Prisma |
| 1004786 | NUMINOS® S , diffuser Ellipse |
| 1006139 | Numinos® S Reducing ring , round 160/100mm black |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1004058 | LED driver , 6.5-10W 250mA |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1006140 | Numinos® S Reducing ring , round 160/100mm white |
| 1006142 | Numinos® S Reducing ring , square 160/100mm white |
| 1004055 | LED driver , 6.5-10W 250mA PHASE |
| 1006141 | Numinos® S Reducing ring , square 160/100mm black |

| | |
|-----------------------|---------|
| Height | 6.35 cm |
| Diameter | 10 cm |
| Net weight | 0.22 kg |
| Gross weight | 0.26 kg |
| Shape of cut-out | round |
| Installation depth | 8.5 cm |
| Installation diameter | 9 cm |
| BIG WHITE Page | 86 |